



3 Type
B without rest position
C with rest position

Rest position with 6 indexing positions (6x30°)

1 d ₁ Plunger h9 Bore $+0,03$ $+0,08$	2 l ₁	b ₁	b ₂	d ₂ -0,15	d ₃	d ₄	k	l ₂	l ₃	l ₄	l ₅ Stroke	Spring load in N ≈		
												initial	end	
4	5	10	35	15	8	21	4,3	25	20,5	2	4	5	4	12
5	6	12	40	18	10	25	4,3	30	25,5	2,5	4	6	6	16
6	6	12	40	18	10	25	4,3	30	25,5	2,5	4	6	6	16
8	10	20	50	23	14	33	5,3	38	35	2,5	5	10	11	35
10	10	20	50	23	14	33	5,3	38	35	2,5	5	10	11	35

Specification

- Socket
Zinc die casting
- corrosion-resistant
ZNDG Pass nano®-coating
- anthracite coloured
- Plunger
Stainless Steel
German Material No. 1.4305
- Spring
Stainless Steel
German Material No. 1.4310
- Knob
Plastic (Polyamide PA)
- black, matt
- not removable
- ISO-Fundamental tolerances → Page xx
- Stainless Steel characteristics → Page xx
- Plastic characteristics → Page xx
- RoHS compliant

Information

Mini indexing plungers GN 822.8 are distinguished for their small dimensions. They are mounted by countersunk screws.

How to order 822.8-6-12-B	1	d ₁
	2	l ₁
	3	Type